


STAINLESS STEEL



Flats

Stainless steel - cold drawn

According to: EN 10277-1, tolerances: h11

Grade according to EN 10088-3

Surface condition: bright

a	t													
	3	4	5	6	8	10	12	15	20	25	30	40	50	60
8	0.19	0.26	0.32	0.38										
10	0.24	0.32	0.40	0.48	0.64									
12	0.29	0.38	0.48	0.58	0.77	0.96								
15	0.36	0.48	0.60	0.72	0.96	1.20	1.44							
16	0.38	0.51	0.64	0.77	1.02	1.28	1.54							
18	0.43	0.58	0.72	0.86	1.15	1.44	1.73	2.16						
20	0.48	0.64	0.80	0.96	1.28	1.60	1.92	2.40						
25	0.60	0.80	1.00	1.20	1.60	2.00	2.40	3.00	4.00					
30	0.72	0.96	1.20	1.44	1.92	2.40	2.88	3.60	4.80	6.00				
35	0.84	1.12	1.40	1.68	2.24	2.80	3.36	4.20	5.60	7.00	8.40			
40	0.96	1.28	1.60	1.92	2.56	3.20	3.84	4.80	6.40	8.00	9.60			
45	1.08	1.44	1.80	2.16	2.88	3.60	4.32	5.40	7.20	9.00	10.80			
50	1.20	1.60	2.00	2.40	3.20	4.00	4.80	6.00	8.00	10.00	12.00	16.00		
60		1.92	2.40	2.88	3.84	4.80	5.76	7.20	9.60	12.00	14.40	19.20		
70		2.24	2.80	3.36	4.48	5.60	6.72	8.40	11.20	14.00	16.80	22.40		
80		2.56	3.20	3.84	5.12	6.40	7.68	9.60	12.80	16.00	19.20	25.60	32.00	38.40
90		2.88	3.60	4.32	5.76	7.20	8.64	10.80	14.40	18.00	21.60	28.80	36.00	43.20
100			4.00	4.80	6.40	8.00	9.60	12.00	16.00	20.00	24.00	32.00	40.00	48.00
110			4.40	5.28	7.04	8.80	10.56	13.20	17.60	22.00	26.40	35.20	44.00	52.80
120				5.76	7.68	9.60	11.52	14.40	19.20	24.00	28.80	38.40	48.00	57.60
125				6.00	8.00	10.00	12.00	15.00	20.00	25.00	30.00	40.00	50.00	60.00
130				6.24	8.32	10.40	12.48	15.60	20.80	26.00	31.20			
140				6.72	8.96	11.20	13.44	16.80	22.40	28.00	33.60			
150				7.20	9.60	12.00	14.40	18.00	24.00	30.00	36.00			
160				7.68	10.24	12.80	15.36	19.20	25.60	32.00	38.40			
180				8.64	11.52	14.40	17.28	21.60	28.80	36.00	43.20			
200				9.60	12.80	16.00	19.20	24.00	32.00	40.00	48.00			
	kg/m													